



POWER UNIT:  
 WITH MINIMUM 4'-0" DEEP PIT THE  
 USABLE OIL FOR TRAVEL WOULD BE  
 36 GALLONS. IF PIT DEPTH IS  
 INCREASED POWER UNIT OIL QTY CAN  
 INCREASE AT 1.2 GALLONS PER INCH  
 OF ADDITIONAL PIT DEPTH.  
 MAX PUMP IS 280 SERIES, MAX  
 MOTOR IS 40 HP (3 PHASE ONLY)

HOISTWAY:  
 FOR MINIMUM HOISTWAY WIDTHS  
 SHOWN THE NOTCH OR POCKET IS  
 REQUIRED AS DIMENSIONED. IF THE  
 NOTCH OR POCKET IS TO BE  
 OMITTED THE HOISTWAY WIDTH  
 MUST INCREASE TO THE MINIMUM  
 HOISTWAY WIDTH WITHOUT NOTCH OR  
 POCKET. THE NOTCH OR POCKET  
 MUST EXTEND VERTICALLY DOWN TO  
 THE PIT FLOOR. THE NOTCH MAY BE  
 THE SAME WIDTH AS THE DOOR WAY.  
 THE WALL THICKNESS FOR THE SIDE  
 CONTAINING THE CONTROL SPACE  
 ACCESS DOOR IS TO BE NO LESS  
 THAN 7 5/8", OTHERWISE THE DOOR  
 WAY WILL NEED TO PROJECT FROM  
 THE REST OF THE WALL SURFACE.

SINGLE SPEED  
 ELEVATOR ENTRANCES MAY BE  
 OPPOSITE OR CENTER PARTING

	DUAL SINGLE STAGE HOLELESS	DUAL TELESCOPIC HOLELESS	STD UNDER CAR WITH WELL HOLE
MAX RISE	20'-0"	34'-0"	35'-0"
SPEED MOTOR	102 FPM 30 HP	100 FPM 25 HP	100 FPM 30 HP
SPEED MOTOR	127 FPM 40 HP	123 FPM 30 HP	124 FPM 40 HP
SPEED MOTOR	146 FPM 40 HP	143 FPM 40 HP	143 FPM 40 HP