



POWER UNIT:
 WITH MINIMUM 4'-0" DEEP PIT THE USABLE OIL FOR TRAVEL WOULD BE 36 GALLONS. IF PIT DEPTH IS INCREASED POWER UNIT OIL QTY CAN INCREASE AT 1.2 GALLONS PER INCH OF ADDITIONAL PIT DEPTH.
 MAX PUMP IS 280 SERIES, MAX MOTOR IS 40 HP (3 PHASE ONLY)

HOISTWAY:
 FOR MINIMUM HOISTWAY WIDTHS SHOWN THE NOTCH OR POCKET IS REQUIRED AS DIMENSIONED. IF THE NOTCH OR POCKET IS TO BE OMITTED THE HOISTWAY WIDTH MUST INCREASE TO THE MINIMUM HOISTWAY WIDTH WITHOUT NOTCH OR POCKET. THE NOTCH OR POCKET MUST EXTEND VERTICALLY DOWN TO THE PIT FLOOR. THE NOTCH MAY BE THE SAME WIDTH AS THE DOOR WAY. THE WALL THICKNESS FOR THE SIDE CONTAINING THE CONTROL SPACE ACCESS DOOR IS TO BE NO LESS THAN 7 5/8", OTHERWISE THE DOOR WAY WILL NEED TO PROJECT FROM THE REST OF THE WALL SURFACE.

SINGLE SPEED
 ELEVATOR ENTRANCES MAY BE OPPOSITE OR CENTER PARTING

	DUAL SINGLE STAGE HOLELESS	DUAL TELESCOPIC HOLELESS	STD UNDER CAR WITH WELL HOLE
MAX RISE	20'-0"	31'-0"	35'-0"
SPEED MOTOR	102 FPM 30 HP	101 FPM 25 HP	100 FPM 30 HP
SPEED MOTOR	127 FPM 40 HP	123 FPM 40 HP	125 FPM 40 HP
SPEED MOTOR	X	142 FPM 40 HP	X