



| | | | | |
|-------------|------------------|-------------------------------|-----------------------------|---------------------------------|
| | | DUAL SINGLE STAGE HOLELESS | DUAL TELESCOPIC HOLELESS | STD UNDER CAR WITH WELL HOLE |
| MAX RISE | 20'-0" | 28'-0" | 29'-0" | |
| SPEED MOTOR | 97 FPM 40 HP | 101 FPM 40 HP | 103 FPM 40 HP | |
| SPEED MOTOR | 111 FPM 40 HP | | | |

POWER UNIT:
WITH MINIMUM 4'-0" DEEP PIT THE USABLE OIL FOR TRAVEL WOULD BE 36 GALLONS. IF PIT DEPTH IS INCREASED POWER UNIT OIL QTY CAN INCREASE AT 1.2 GALLONS PER INCH OF ADDITIONAL PIT DEPTH.
MAX PUMP IS 280 SERIES. MAX MOTOR IS 40 HP (3 PHASE ONLY)

HOISTWAY:
FOR MINIMUM HOISTWAY WIDTHS SHOWN THE NOTCH OR POCKET IS REQUIRED AS DIMENSIONED. IF THE NOTCH OR POCKET IS TO BE OMITTED THE HOISTWAY WIDTH MUST INCREASE TO THE MINIMUM HOISTWAY WIDTH WITHOUT NOTCH OR POCKET. THE NOTCH OR POCKET MUST EXTEND VERTICALLY DOWN TO THE PIT FLOOR. THE NOTCH MAY BE THE SAME WIDTH AS THE DOOR WAY. THE WALL THICKNESS FOR THE SIDE CONTAINING THE CONTROL SPACE ACCESS DOOR IS TO BE NO LESS THAN 7 5/8", OTHERWISE THE DOOR WAY WILL NEED TO PROJECT FROM THE REST OF THE WALL SURFACE.

TWO SPEED
ELEVATOR ENTRANCES MAY BE OPPOSITE HAND